

SWP-CI BIG RED Curb Inlet Protector

Product Reference



The Midwest's Most Trusted
Site Solutions Provider

GEO SOURCE

Product

The SWP-CI "Big Red" Filter is a REUSABLE inlet protector that keeps out sediment throughout the entire construction project. There are no pockets to fill, no velcro bags, no assembly etc. Simply place in front of the inlet, make sure it lays in the contour, and you are DONE!

"Big Red" CI Protector Advantages:

- Easy to Install
- Versatile for a variety of curb inlets
- Reusable and Extremely easy to clean
- Made from 90% Inert Recycled Materials



1 "Big Red" CI protector protecting a concrete swale.

Fabric Properties

Property	Test	Units	Value
Weight	ASTM D5261	oz/sq yd	9.3
Grab Tensile Strength	ASTM D4632	lb	warp 250 fill 290
Tear Strength	ASTM D4533	lb	warp 60 fill 50
Burst	ASTM D3786	psi	440

Installation

Simple installation also translates into simple removal, cleanup and re-use at the next project or phase. Maintenance is simple as well by lifting the unit from the inlet, shaking the mud off of it, removing the sediment on the concrete, and placing the unit back. If it is severely filled with sediment, wash it out in a vegetated area and it is as good as new.

All of these features and benefits combine to make the SWP-CI "Big Red" curb inlet protector the perfect choice for all curb inlet applications. It comes in 54" long for single curb inlets and 104" lengths for double curb inlets. Custom sizes are also available depending on quantity.



2 This is a 14' custom unit. Big Red is very easy to work with.



3 Single "Big Red" CI Protector.

product reference

SWP-CI BIG RED Area Inlet Protector

Product Reference



The Midwest's Most Trusted
Site Solutions Provider

GEO SOURCE

Product

The Big Red Area Inlet Protector is a REUSABLE area inlet protector that keeps out sediment throughout the entire construction project. The Big Red Area Inlet Protector is made of highly durable permeable fabric and stiff iron supports to last as long as you need it. For correct installation, trenching the bottom 6 inches is critical.



"Big Red" AI Protector, recently installed with trenched in bottom and tight sides.

Fabric Properties

Property	Test	Units	Value
Weight	ASTM D5261	oz/sq yd	9.3
Grab Tensile Strength	ASTM D4632	lb	warp 250 fill 290
Tear Strength	ASTM D4533	lb	warp 60 fill 50
Burst	ASTM D3786	psi	440
Overall Size			60"x60"

Installation

Simple installation also translates into simple removal, cleanup and re-use at the next project or phase. Maintenance is simple as well by digging away the sediment in front of the protector. If necessary, remove the steel support rods, knocking off the dirt and reinstall. If it is severely plugged with sediment, wash it off in a vegetated area and it is as good as new.



"Big Red AI Protector with 4" sediment load after initial Rain Event.

Company Information

ASP Enterprises, Inc. and Quick Supply Co. For more than three decades, A.S.P. Enterprises and Quick Supply Co. has served the erosion control industry with integrity and expertise. We provide engineers and landscape contractors the exceptional value for their money and have grown to become the Midwest's full-line distributor of erosion-control, geosynthetics, storm water management products, wall block, landscape pavers, and drainage products.

ASP Enterprises, Inc.
Corporate
Headquarters
www.aspent.com

St. Louis, MO
636.343.4357
800.869.9600

Quick Supply Co.
Corporate
Headquarters
www.quicksupplydm.com

Des Moines, IA
515.289.1271
800.362.2245

Kansas City, MO
816.554.1191
800.519.2304

Omaha, NE
402.8618579
877.678.8027

Wichita, KS
316.393.1554