



**ROLLMAX™**  
ROLLED EROSION CONTROL

## Specification Sheet – BioNet® C125BN™ Erosion Control Blanket

### DESCRIPTION

The long-term double net erosion control blanket shall be a machine-produced mat of 100% coconut fiber with a functional longevity of up to 24 months. (NOTE: functional longevity may vary depending upon climatic conditions, soil, geographical location, and elevation). The blanket shall be of consistent thickness with the coconut evenly distributed over the entire area of the mat. The blanket shall be covered on the top and bottom sides with 100% biodegradable woven natural organic fiber netting. The netting shall consist of machine directional strands formed from two intertwined yarns with cross directional strands interwoven through the the twisted machine strands (commonly referred to as Leno weave) to form an approximate 0.50 x 1.0 in (1.27 x 2.54 cm) mesh. The blanket shall be sewn together on 1.50 inch (3.81 cm) centers with degradable thread. The blanket shall be manufactured with a colored thread stitched along both outer edges (approximately 2-5 inches [5-12.5 cm] from the edge) as an overlap guide for adjacent mats.

The C125BN shall meet Type 4 specification requirements established by the Erosion Control Technology Council (ECTC) and Federal Highway Administration's (FHWA) FP-03 Section 713.17

### Material Content

<b>Matrix</b>	100% Coconut Fiber	0.5 lbs/sq yd (0.27 kg/sm)
	Leno Woven 100% biodegradable jute	9.3 lbs/1000 sq ft (4.5 kg/100 sm)
<b>Netting</b>	100% Biodegradable jute	7.7 lb/1000 sq ft (3.76 kg/100 sm)
<b>Thread</b>	Black polypropylene	

### Standard Roll Sizes

<b>Width</b>	6.67 (2.03 m)	8.0 ft (2.4 m)
<b>Length</b>	108 ft (32.92 m)	112 ft (34.14 m)
<b>Weight ± 10%</b>	52.22 lbs (23.69 kg)	65.25 lbs (29.61 kg)
<b>Area</b>	80 sq yd (66.9 sm)	100 sq yd (83.61 sm)
	Leno weave top only	Leno weave top and bottom

Index Property	Test Method	Typical
<b>Thickness</b>	ASTM D6525	0.23 in. (5.84 mm)
<b>Resiliency</b>	ECTC Guidelines	85%
<b>Water Absorbency</b>	ASTM D1117	365%
<b>Mass/Unit Area</b>	ASTM 6475	9.79 oz/sy (333 g/sm)
<b>Swell</b>	ECTC Guidelines	40%
<b>Smolder Resistance</b>	ECTC Guidelines	Yes
<b>Stiffness</b>	ASTM D1388	0.11 oz-in
<b>Light Penetration</b>	ASTM D6567	16.2%
<b>Tensile Strength - MD</b>	ASTM D6818	206.4 lbs/ft (3.06 kN/m)
<b>Elongation - MD</b>	ASTM D6818	15.3%
<b>Tensile Strength - TD</b>	ASTM D6818	145.2 lbs/ft (2.15 kN/m)
<b>Elongation - TD</b>	ASTM D6818	12.9%
<b>Biomass Improvement</b>	ASTM 7322	473%

### Design Permissible Shear Stress

<b>Unvegetated Shear Stress</b>	2.35 psf (112 Pa)
<b>Unvegetated Velocity</b>	10.0 fps (3.05 m/s)

### Slope Design Data: C Factors

Slope Gradients (S)			
Slope Length (L)	≤ 3:1	3:1 – 2:1	≥ 2:1
≤ 20 ft (6 m)	0.0001	0.018	0.050
20-50 ft	0.003	0.040	0.060
≥ 50 ft (15.2 m)	0.007	0.070	0.070

### Roughness Coefficients – Unveg.

Flow Depth	Manning's n
≤ 0.50 ft (0.15 m)	0.022
0.50 – 2.0 ft	0.022-0.014
≥ 2.0 ft (0.60 m)	0.014

Distributed by: ASP Enterprises-STL: 1099 Cassens Industrial Ct., Fenton, MO 63026, Phone: 800-869-9600, [www.aspent.com](http://www.aspent.com)  
 ASP Enterprises-KC: 5301 E. 59th St., Kansas City, MO 64130, Phone 800-519-2304, [www.aspent.com](http://www.aspent.com)  
 ASP Enterprises-Omaha: 15263 Cooper Street, Omaha, NE 68138 Phone: 877-678-8027, [www.aspent.com](http://www.aspent.com)



**Tensar**®

**NORTH AMERICAN GREEN®**

Tensar International Corporation  
 2500 Northwinds Parkway  
 Suite 500  
 Alpharetta, GA 30009  
 800-TENSAR-1  
[tensarcorp.com](http://tensarcorp.com)

Tensar International Corporation warrants that at the time of delivery the product furnished hereunder shall conform to the specification stated herein. Any other warranty including merchantability and fitness for a particular purpose, are hereby executed. If the product does not meet specifications on this page and Tensar is notified prior to installation, Tensar will replace the product at no cost to the customer. **This product specification supersedes all prior specifications for the product described above and is not applicable to any products shipped prior to January 1, 2012.**

©2013, Tensar International Corporation

EC\_RMX\_MPDS\_BC125BN\_5.13