



FLEXAMAT INFORMATION

Manufacturer: Motz Enterprises, Inc.
 Product Name: Flexamat®
 Address: 3153 Madison Road
 Cincinnati, Ohio 45209
 Telephone: 513-772-MOTZ (6689)
 Fax: 513-772-6690
 Contact: Matt Motz
 Email: Matt@Flexamat.com
 Website: www.Flexamat.com

CONSTRUCTION NOTES:

1. GRADE OUTFALL AREA SO THAT WATER WILL FLOW DOWN THE CENTER OF THE CHANNEL AND BE CONTAINED TO THE CHANNEL. ALL SUBGRADE SURFACES PREPARED FOR PLACEMENT OF MATS SHALL BE SMOOTH AND FREE OF ALL ROCKS, STICKS, ROOTS, OTHER PROTRUSIONS, OR DEBRIS OF ANY KIND. THE PREPARED SURFACE SHALL PROVIDE A FIRM UNYIELDING FOUNDATION FOR THE MATS WITH NO SHARP OR ABRUPT BREAKS IN THE GRADE .
2. APPLY SEED DIRECTLY TO THE PREPARED SOIL PRIOR TO FLEXAMAT INSTALLATION. USE SEED PER PROJECT SPECIFICATIONS.
3. PRIOR TO INSTALLING HEADWALL, ANCHOR TRENCH INITIAL LEADING EDGE OF MAT 18", FILL AND COMPACT ANCHOR TRENCH. INSTALL HEADWALL OVER MAT.
4. INSTALL FLEXAMAT ROLLS. AVAILABLE WIDTHS ARE 5.5', 8', 10', 12', & 16' AVAILABLE IN CUSTOM LENGTHS. A CONCRETE SAW SHALL BE USED TO CUT THE MAT TO EXACT SIZE AND SHAPE.
5. APPLICATIONS WHERE OUTFALLS FLOW INTO RETENTION PONDS, EXTEND FLEXAMAT A MINIMUM OF 3' BELOW LOW WATER ELEVATION.

DISTRIBUTOR



ASP Enterprises-STL
 1099 Cassens Ind. Ct.
 Fenton, MO 63026
 TF: 800-869-9600
www.aspent.com

ASP Enterprises-KC
 5301 E. 59th St.
 Kansas City, MO 64130
 TF: 800-519-2304
www.aspent.com

ASP Enterprises-Omaha
 15263 Cooper St.
 Omaha, NE 68138
 TF: 877-678-8027
www.aspent.com

FLEXAMAT®
 NEW OUTLET INSTALLATION
 DETAIL