

KEYSTONE STANDARD® STRAIGHT

PRODUCT NUMBER # 110173



- Crisp and distinctive, the straight split face effectively showcases the color within each unit
- Installed with 1/2in diameter, pultruded fiberglass pins. Allowing for a near vertical or setback installation, Keystone interlocking pins improve interaction with geosynthetic textiles and feature 6,400 psi shear strength
- Superposed webs make core-filling fast and complete, best-in-class weight and rounded grips make handling safer and easier
- Low batter maximizes buildable site area
- Made of durable concrete with iron oxide pigments that resist fading in extended UV exposure. Meets or exceeds applicable requirements of ASTM C1372

The product that started the retaining wall industry is still the industry leader for tall walls and critical structures. The Keystone Standard unit's depth provides unrivaled structural stability. From backyard landscaping to large, load-bearing reinforced structures, the Keystone Standard unit's face styles, colors and design possibilities make it a favorite of architects and engineers worldwide.

STONE(S)



| | Wall | | |
|---------------|------------|-----|-------|
| Height | <i>in</i> | In. | 8 |
| | <i>mm</i> | MM. | 203.2 |
| Length | <i>in</i> | IN. | 21 |
| | <i>mm</i> | MM | 533.4 |
| Width | <i>in</i> | IN | 18 |
| | <i>mm</i> | MM | 457.2 |
| Units | <i>/pl</i> | QTY | 24 |

PALLET LAYOUT

□

NOTES

Weights are approximate and do not include shipping pallet. Installation to applicable NCMA standards is required for warranty coverage. Made with natural materials, which vary in color, and Portland cement, which may effloresce - any implied warranty to the contrary is disclaimed.

PALLET SPECS

| | |
|----------------------|-----------|
| Pallet Weight | 2345 lbs |
| Sq Ft/Pallet | 24 sq.ft. |



Distributed by:



www.aspent.com

(800) 869-9600

www.pavestone.com

KEYSTONE STANDARD® ROCKFACE

PRODUCT NUMBER # 110174



- Rugged exterior evokes the look and feel of naturally weathered stone
- Installed with 1/2in diameter, pultruded fiberglass pins. Allowing for a near vertical or setback installation, Keystone interlocking pins improve interaction with geosynthetic textiles and feature 6,400 psi shear strength
- Superposed webs make core-filling fast and complete, best-in-class weight and rounded grips make handling safer and easier
- Low batter maximizes buildable site area
- Made of durable concrete with iron oxide pigments that resist fading in extended UV exposure. Meets or exceeds applicable requirements of ASTM C1372

The product that started the retaining wall industry is still the industry leader for tall walls and critical structures. The Keystone Standard unit's depth provides unrivaled structural stability. From backyard landscaping to large, load-bearing reinforced structures, the Keystone Standard unit's face styles, colors and design possibilities make it a favorite of architects and engineers worldwide.

STONE(S)



| | | | Wall |
|---------------|------------|-----|-------|
| Height | <i>in</i> | In. | 8 |
| | <i>mm</i> | MM. | 203.2 |
| Length | <i>in</i> | IN. | 21 |
| | <i>mm</i> | MM | 533.4 |
| Width | <i>in</i> | IN | 18 |
| | <i>mm</i> | MM | 457.2 |
| Units | <i>/pl</i> | QTY | 24 |

PALLET LAYOUT

□

NOTES

Weights are approximate and do not include shipping pallet. Installation to applicable NCMA standards is required for warranty coverage. Made with natural materials, which vary in color, and Portland cement, which may effloresce - any implied warranty to the contrary is disclaimed.

PALLET SPECS

| | |
|----------------------|-----------|
| Pallet Weight | 2345 lbs |
| Sq Ft/Pallet | 24 sq.ft. |

KEYSTONE STANDARD® MEDLEY

PRODUCT NUMBER # 110175



- Scored and straight split units combine to achieve the beauty of a three-piece stone system with the efficiencies of a single unit installation
- Installed with 1/2in diameter, pultruded fiberglass pins. Allowing for a near vertical or setback installation, Keystone interlocking pins improve interaction with geosynthetic textiles and feature 6,400 psi shear strength
- Superposed webs make core-filling fast and complete, best-in-class weight and rounded grips make handling safer and easier
- Low batter maximizes buildable site area
- Made of durable concrete with iron oxide pigments that resist fading in extended UV exposure. Meets or exceeds applicable requirements of ASTM C1372

The product that started the retaining wall industry is still the industry leader for tall walls and critical structures. The Keystone Standard unit's depth provides unrivaled structural stability. From backyard landscaping to large, load-bearing reinforced structures, the Keystone Standard unit's face styles, colors and design possibilities make it a favorite of architects and engineers worldwide.

STONE(S)

| | Wall | | |
|---------------|------------|-----|-------|
| Height | <i>in</i> | In. | 8 |
| | <i>mm</i> | MM. | 203.2 |
| Length | <i>in</i> | IN. | 21 |
| | <i>mm</i> | MM | 533.4 |
| Width | <i>in</i> | IN | 18 |
| | <i>mm</i> | MM | 457.2 |
| Units | <i>/pl</i> | QTY | 24 |

PALLET LAYOUT

□

NOTES

Weights are approximate and do not include shipping pallet. Installation to applicable NCMA standards is required for warranty coverage. Made with natural materials, which vary in color, and Portland cement, which may effloresce - any implied warranty to the contrary is disclaimed.

PALLET SPECS

| | |
|----------------------|-----------|
| Pallet Weight | 2273 lbs |
| Sq Ft/Pallet | 24 sq.ft. |