




# Info

**DESCRIPTION:** Paver **TEXTURE:** Smooth

## PALLET OVERVIEW



- LEED® Projects.
- Reduces stormwater runoff to municipal sewers.
- Eliminates the need for retention basins and optimizes the use of land.


## CHARACTERISTICS

- Mechanical connection (tongue and groove system).
- 6000 to 8000 sq. ft can be installed per day with the TB100SI and a team of 5 persons.
- Maintains its interlocking properties, over time and under heavy traffic loads.

## NOTES

See page 87 to 93 for more technical information.

### 01 | Linear pattern



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.



Specifications per pallet	Imperial	Metric
Cubing	62 ft <sup>2</sup>	5.76 m <sup>2</sup>
Weight	2 710 lbs	1 229 kg
Number of rows	8	
Coverage per row	7.75 ft <sup>2</sup>	0.72 m <sup>2</sup>
Linear coverage per row	11.80 lin. ft	3.60 lin. m
Percent of surface opening	5.8%	
Joint Width	1/2"	13 mm

Unit dimensions	in		mm		Units/pallet
	H	D	A		
Height	3 15/16	100			96 units
Depth	7 7/8	200			
Length	11 13/16	300			



Distributed by:

www.aspent.com (800) 869-9600